

| | |
|----------------------------------|---|
| 定位精度 Positioning accuracy | 2M 3M 160M |
| 速度精度 Speed accuracy | 150Mbps 433.3Mbps 72.2 Mbps |
| 天线类型 Antenna type | IPEX 外接天线 IPEX external antenna PCB 板载天线 PCB onboard antenna 单外置天线 Single external antenna 外置双天线 External dual antenna 外接线 External cable |
| 发射功率 Transmit power | 18dBm 19.5dBm 16dBm 15dBm 17dBm 14dbm |
| 封装方式 Packaging method | SMD QFN LGA |
| 类型 Type | IoT module Smart home module Remote control Audio module Power amplifier module Sensor module Other modules |
| 应用领域 Application areas | Consumer Electronics Standard Smart home Communication Other |
| 是否定制 Whether to customize | Customizable |
| 机械刚性 Mechanical rigidity | Rigid& flexible |
| 层数 Number of layers | Double sided Single sided |
| 基材 Base material | Copper Aluminum Nickel |
| 阻燃特 Flame retardant properties | VO board & HB board |
| 绝缘层厚度 Insulation layer thickness | Conventional board & Thin board |
| 加工工艺 Processing technology | Electrolytic foil & Calendered foil |
| 无线标准 Wireless standards | IEEE 802.11G IEEE 802.11B IEEE 802.11N |
| 绝缘树脂 Insulating resin | Phenolic Resin Epoxy resin (EP) |
| 工作电压 Operating Voltage | 3.3V 5V 12V |
| 灵敏度 Sensitivity | Standard |
| 外形尺寸 Dimensions | Standard |